



Size	L	D	D1	D2	b	n-d	H(open)	W	W.T(kg)
DN40	140	150	110	84	18	4-19	340	180	13
DN50	150	165	125	99	20	4-19	354	180	14
DN65	170	185	145	118	20	4-19	390	180	18.5
DN80	180	200	160	132	22	8-19	435	200	25.1
DN100	190	220	180	156	24	8-19	545	200	32.3
DN125	200	250	210	184	26	8-19	625	250	44.6
DN150	210	285	240	211	26	8-23	750	280	59.2
DN200	230	340	295	266	26	8-23	980	300	88
DN250	250	395	350	319	28	12-23	1130	360	138
DN300	270	445	400	370	28	12-23	1330	400	177.5
DN350	290	505	460	429	30	16-23	1533	450	240
DN400	310	565	515	480	32	16-28	1905	450	420
DN450	330	615	565	530	32	20-28	2072	640	485
DN500	350	670	620	582	34	20-28	2302	640	650
DN600	390	780	725	682	36	20-31	2650	900	920

Item	Part Name	Material	Item	Part Name	Material
1	Body	EN-GJL-250	7	Bonnet Gasket	Graphite
2	Seat Ring	Brass	9	Bonnet	EN-GJL-250
3	Wedge	EN-GJL-250	9a	Yoke	EN-GJL-250
4	Wedge Ring	Brass	11	Packing	Graphite
6	Stem	AISI 420	14	Gland Follower	EN-GJS-500-7

**Design Specification**  
 Design confirm to DIN3352  
 Connections confirm to EN 1092-2  
 Face to face confirm to DIN3202 F4  
 Pressure Rating: PN16

DN40-DN600 DIN3352 F4 RS Gate Valve



DWG NO. B600RMGV

