



Size	L	D	D1	D2	b	n-d	H(open)	W	W.T(kg)
DN40	240	150	110	84	18	4-19	340	180	15
DN50	250	165	125	99	20	4-19	354	180	17.3
DN65	270	185	145	118	20	4-19	390	180	21.5
DN80	280	200	160	132	22	8-19	435	200	28.1
DN100	300	220	180	156	24	8-19	545	200	35.9
DN125	325	250	210	184	26	8-19	625	250	50.6
DN150	350	285	240	211	26	8-23	750	280	71.2
DN200	400	340	295	266	30	12-23	980	300	83
DN250	450	405	355	319	32	12-28	1130	360	147
DN300	500	460	410	370	32	12-28	1330	400	210
DN350	550	520	470	429	36	16-28	1533	450	280
DN400	600	580	525	480	38	16-31	1905	450	487.2
DN450	650	640	585	548	40	20-31	2072	640	562.6
DN500	700	715	650	609	42	20-34	2302	640	754.0
DN600	800	840	770	720	48	20-37	2650	900	1067.2

Item	Part Name	Material	Item	Part Name	Material
1	Body	EN-GJL-250	7	Bonnet Gasket	Graphite
2	Seat Ring	Brass	10	Bonnet	EN-GJL-250
3	Wedge	EN-GJL-250	10a	Yoke	EN-GJL-250
4	Wedge Ring	Brass	12	Packing	Graphite
6	Stem	AISI 420	14	Gland Follower	EN-GJL-250

Design Specification
 Design confirm to DIN3352
 Connections confirm to EN 1092-2
 Face to face confirm to DIN3202 F5
 Pressure Rating: PN16

DN40-DN600 DIN3352 F5 RS Gate Valve



DWG NO. B600RMGV

