



SIZE		L	H1	H2	H3	ISO5211				ANSI 125/150		DIN2501 PN10		DIN2501 PN16		ØZ	ØF	H
DN	NPS					No.	ØN	ØC1	n1-Ød1	ØC	n-Ød	ØC	n-Ød	ØC	n-Ød			
50	2"	43	143	55	29	F05	65	50	4-Ø8	/	/	/	/	125	4-Ø18	12.6	12.1	9
65	2-1/2"	46	155	64	29	F05	65	50	4-Ø8	/	/	/	/	145	4-Ø18	12.6	12.1	9
80	3"	46	162	72	29	F05	65	50	4-Ø8	/	/	/	/	160	8-Ø18	12.6	12.1	9
100	4"	52	181	90	29	F07	90	70	4-Ø10	/	/	/	/	180	8-Ø18	15.77	14.1	11
125	5"	56	197	101	29	F07	90	70	4-Ø10	/	/	/	/	210	8-Ø18	18.92	18.1	14
150	6"	56	210	114	29	F07	90	70	4-Ø10	/	/	/	/	240	8-Ø22	18.92	18.1	14
200	8"	60	240	145	35	F10	125	102	4-Ø12	/	/	/	/	295	12-Ø22	22.1	22.1	17
250	10"	68	286	178	35	F10	125	102	4-Ø12	/	/	/	/	355	12-Ø26	28.45	28.2	22
300	12"	78	309	204	35	F10	125	102	4-Ø12	/	/	/	/	410	12-Ø26	31.6	28.2	22
350	14"	78	328	264	45	F10	125	102	4-Ø12	476.2	12-28.4	460	16-22	470	16-26	31.6	28.2	22
400	16"	102	360	293	51.2	F14	175	140	4-Ø18	539.7	16-28.4	515	16-26	525	16-30	33.15	28.2	22
450	18"	114	400	324	51.2	F14	175	140	4-Ø18	577.8	16-31.8	565	20-26	585	20-30	38	36.2	27
500	20"	127	460	350	64.2	F14	175	140	4-Ø18	635	20-31.8	620	20-26	650	20-33	41.15	36.2	27
600	24"	154	540	440	70.2	F16	210	165	4-Ø22	749.3	20-35.1	725	20-30	770	20-36	50.65	48.2	36

DN40-DN600 B20 Wafer Type Butterfly Valve With Pin

DWG NO. WBWP20